(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 30 September 2004 (30.09.2004)

PCT

(10) International Publication Number WO 2004/083645 A2

(51) International Patent Classification7:

F15B

(21) International Application Number:

PCT/US2004/008638

(22) International Filing Date: 18 March 2004 (18.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/455,999

18 March 2003 (18.03.2003) US

(71) Applicant and

(72) Inventor: LAST, Harry, J. [US/US]; 1010 Koohoo Place, Kailua, HI 96734 (US).

(74) Agent: NEWHOUSE, David, E.; 477 Ninth Ave., Suite 112, San Mateo, CA 94402 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU. TJ. TM), European (AT, BE, BG, CH, CY, CZ. DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DUAL, COUPLED CHECK VALVE FOR DIRECT DRIVE, REVERSIBLE POWER SOURCES FOR HYDRAULIC SYSTEMS

(57) Abstract: An invented dual, coupled check valve mechanism is described for a direct drive, reversible hydraulic power source for hydraulic circuits that includes a manifold hydraulically coupled to the respective input/output ports and a reservoir of the hydraulic power source defining a translation passageway having mid-passage drain hydraulically coupled to the reservoir, where each end of the translation passageway has an angled annular valve seat opening to larger diameter plenum containing a check valve ball. A translating rod with a length greater and a circumferential diameter less than that of the translation passageway located in the translation passageway prevents the respective check valve balls from simultaneously seating on the valve seats at the respective ends of the translation passage way.

